

HIPPO[®] TURBINES

Recommended Sizes for Coiled Tubing



HAMDEEN

©2002

	Wall Thickness (Inches)	Coarse Size (HTC)	Finishing Size (HTP)
1 1/4" CT	0.175	20	23
	0.156	21	24
	0.134	22	25
	0.125	22	25
	0.118	23	26
	0.109	23	26
	0.102	24	27
	0.095	24	27
	0.087	24	27
1 1/2" CT	0.188	25	28
	0.175	26	29
	0.156	27	30
	0.134	28	31
	0.125	29	32
	0.118	29	32
	0.109	30	33
	0.102	30	33
	0.095	30	33
1 3/4" CT	0.188	32	35
	0.175	33	36
	0.156	33	36
	0.134	35	38
	0.125	35	38
	0.118	35	38
	0.109	36	39
2" CT	0.203	37	40
	0.188	38	41
	0.175	39	42
	0.156	40	43
	0.134	41	44
	0.125	41	44
	0.118	42	45
	0.109	42	45
2 3/8" CT	0.203	47	50
	0.188	48	51
	0.175	48	51
	0.156	49	52
	0.134	50	53
	0.125	51	54
	0.118	51	54
	0.109	52	55

Note:

1. Make Hippo sizes selection based on the heaviest wall section
2. For Hippo application please refer to Hamdeen procedures

Hamdeen (UK) Ltd, Unit 4, Blackness Ind. Centre, Blackness Road, Altens, Aberdeen, AB12 3LH, SCOTLAND
 Tel: +44 (0)1224 245100 Fax: +44 (0)1224 245101 Email: sales@hamdeen.com

DS006 Rev 0